

WISI OH 50 R

Compact Headend basic unit, 230 V AC (redundantly), 19", 3 HE, for 14 modules



Description

At a glance:

- Base unit OH 50 for analog und digital channel processing headends
- Slots for up to 14 modules (14 analog or 28 digital channels)
- included Additional power supply 230 VAC for redundancy
- 19" rack-mounting or wall mounting
- Integrated FM amplifier
- Simple programming with handset OH 41 (OK 41 A)
- Preprogramming via USB-connection (USB-Stick)
- Integrated remote supervision moduel OH 51 A (license optional)
- High output power

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 28. Januar 2015, 3:15 nachm.

Technical data

Frequency range TV	47...862 MHz (output combiner/ amplifier)
Frequency range FM	87,5...108 MHz (FM-amplifier)
Input level FM	70...100 dBμV
Gain FM	25 dB
Attenuator FM	30 dB (1 dB-steps)
Output level	110 dBμV
Output attenuator	0...15 dB
Output test jack	-20 dB

Connectors

Module slots	14 pcs. (OH-module)
F-socket	3 pcs. (FM-input, output, output measurement socket)
USB	1 pcs. (Software-Update, Konfi- guration)
RJ11	1 pcs. (OH 41)
RJ45	1 pcs. (remote monitoring and programming)

General data

Operating voltage AC	180...265 V (47...63 Hz)
redundant power supply	1 pcs.
Power consumption	<185 W
LNB supply voltage	12.5 V
LNB electrical power supply	1.2 A
Dimensions (width x height x depth)	443x132x351 mm (3 HE)
Operating temperature range	-20...+50 °C

Packaging data

Sales unit	1 pcs.
Packaging volume shipping package	31.5 dm³
Gross weight shipping unit	7.64 kg
EAN	4010056740108
Article number	74010
Customs tariff number	85437090